

Steel ball valves, reduced bore

welding / welding, GOST, DN 10-250, reduced bore

Body	DN 10-250 Steel, P235GH (1.0345)
Ball	DN 10-250 Stainless steel, X5CrNi18-10 (1.4301)
Ball seal	DN 10-250 PTFE+C
Stem	DN 10-250 Stainless steel, X8CrNiS18-9 (1.4305)
Stem seal	DN 10-250 FPM
Operation	DN 10-250 With zinc-plated steel handle




Operation conditions
-20 °C – +200 °C
Below -20 °C contact manufacturer
Lowest allowed ambient temperature -40 °C

Leakage rate A (EN 12266-1)




Not for steam

DN 65-150



DN 200-250



DN	PN	Product no.	A	D	D1	D2	H	H1	L	S	kg
10	40	284402/GS	145	10	17.0	33.7	98	22	230	2	0.7
15	40	284403/GS	145	10	18.0	33.7	98	22	230	2	0.6
20	40	284405/GS	145	15	25.0	42.4	103	23	230	2,3	0.8
25	40	284406/GS	145	20	32.0	48.3	118	34	230	2,6	1.0
32	40	284407/GS	145	25	38.0	60.3	121	33	260	2,6	1.4
40	40	284408/GS	188	32	45.0	70.0	120	43	260	2,6	1.7
50	40	284409/GS	188	40	57.0	88.9	127	44	300	2,9	2.6
65	25	284410/GS	277,5	50	76.0	101.6	159	62	300	2,9	4.0
80	25	284411/GS	277,5	65	89.0	121.0	171	68	300	3,2	5.4
100	25	284412/GS	278,5	80	108.0	139.7	218	101	325	3,6	8.4
125	25	284413/GS	400	100	133.0	177.8	252	101	325	4	13.0
150	25	284414/GS	600	125	159.0	219.1	272	107	350	5,0	18.0
200	25	284416/GS	870	150	219.0	273.0	280	92	400	6,0	38.0
250	25	284417/GS	1200	200	273.0	355.6	350	108	530	6	74.0

Steel ball valves, reduced bore


welding / welding, GOST, DN 300-500, reduced bore

Body	DN 300-500 Steel, P235GH (1.0345)
Ball	DN 300-500 Stainless steel, X5CrNi18-10 (1.4301)
Ball seal	DN 300-500 PTFE+C
Stem	DN 300-500 Stainless steel, X8CrNiS18-9 (1.4305)
Stem seal	DN 300-500 FPM
Operation	DN 300-500 Valves are available with manual gear or with an electric or hydraulic actuator



Operation conditions
-20 °C – +200 °C
Below -20 °C contact manufacturer
Lowest allowed ambient temperature -40 °C

Leakage rate A (EN 12266-1)
Not for steam



DN	PN	Product no.	D	D1	D2	D3	H1	L	S	kg
300	25	28443805/GS	250	325.0	457.0	50.0	133	550	7	110.0
350	25	28449505/GS	290	377.0	508.0	50.0	181	686	7,0	170.0
400	25	28443905/GS	340	426.0	610.0	70.0	232	762	7	250.0
500	25	28444005/GS	390	530.0	660.0	90.0	248	914	7	400.0