

Gas ball valves, reduced bore

flange / flange, DN 65-250, reduced bore

Body	DN 65-250 Steel, P235GH (1.0345)
Ball	DN 65-250 Stainless steel, X5CrNi18-10 (1.4301)
Ball seal	DN 65-250 PTFE+C
Stem	DN 65-250 Stainless steel, X8CrNiS18-9 (1.4305)
Stem seal	DN 65-250 NBR
Operation	DN 65-250 With zinc-plated steel handle
Flanges	EN 1092-1
	Available PN 10, 16, 25, 40




Operation conditions
-40 °C – +70 °C
Over 70 °C contact manufacturer
Below -30 °C contact manufacturer
Lowest allowed ambient temperature -40 °C
Leakage rate A (EN 12266-1)




Not for steam

DN 65-150



DN 200-250



DN	PN	Product no.	A	D	D1	D2	D3	H	H1	L	kg
65	16	280510	277,5	50	185.0	145.0	18.0	159	62	270	10.5
80	16	280511	277,5	65	200.0	160.0	18.0	171	68	280	12.5
100	16	280512	278,5	80	220.0	180.0	18.0	218	101	300	17.0
125	16	280513	400	100	250.0	210.0	18.0	252	101	325	25.0
150	16	280514	600	125	285.0	240.0	22.0	272	107	350	33.0
200	16	280516	870	150	340.0	295.0	22.0	280	92	400	58.0
250	16	280517	1200	200	405.0	355.0	26.0	350	108	500	102.0


Gas ball valves, reduced bore

flange / flange, DN 300-500, reduced bore

Body	DN 300-500 Steel, P235GH (1.0345)
Ball	DN 300-500 Stainless steel, X5CrNi18-10 (1.4301)
Ball seal	DN 300-500 PTFE+C
Stem	DN 300-500 Stainless steel, X8CrNiS18-9 (1.4305)
Stem seal	DN 300-500 NBR
Operation	DN 300-500 Valves are available with manual gear or with an electric or hydraulic actuator
Flanges	EN 1092-1 Available PN 10, 16, 25, 40




Operation conditions
-40 °C – +70 °C
Over 70 °C contact manufacturer
Below -30 °C contact manufacturer
Lowest allowed ambient temperature -40 °C
Leakage rate A (EN 12266-1)




Not for steam

DN 300-600



DN 300-600



DN	PN	Product no.	D	D1	D2	D3	D4	H1	L	kg
300	16	28053805	250	460.0	410.0	26.0	50.0	133	500	148.0
350	16	28054505	290	520.0	470.0	26.0	50.0	192	706	226.0
400	16	28053905	340	580.0	525.0	30.0	70.0	242	810	322.0
500	16	28054005	390	715.0	650.0	33.0	90.0	259	978	528.0