

Underground ball valves, reduced bore

231XI series, air release valve / short, X-series, female threads / welding EN (DIN), DN 25-50, reduced bore


Body	DN 25-50 Stainless steel, X2CrNiMo17-12-2 (1.4404)
Extension Pipe	DN 25-50 Steel, P235GH (1.0345)
Ball	DN 25-50 Stainless steel, X2CrNiMo17-12-2 (1.4404)
Ball seal	DN 25-50 PTFE+C
Stem	DN 25-50 Stainless steel, X2CrNiMo17-12-2 (1.4404)
Stem seal	DN 25-50 FPM/NBR
Plug	DN 25-50 DZR brass
Equipment	DN 25-50 are equipped with plug



Operation conditions


-20 °C – +200 °C
Below -20 °C contact manufacturer
Lowest allowed ambient temperature -40 °C

Leakage rate A (EN 12266-1)



Not for steam

DN 25-50



DN	PN	Product no.	D	D1	D2	H	H1	HEX	HEX19	L	L1	L2	L3	R	S	kg
25	25	231025X/I	20	33.7	48.3	82	23	19	19	412	395	338	255	1"	4	1.8
40	25	231040X/I	32	48.3	70.0	91	24	27	19	416	395	319	215	1 1/2"	4,5	3.0
50	25	231050X/I	40	60.3	76.1	98	25	27	19	416	392	303	194	2"	4	3.8