

Gaskulventiler, reducerat genomlopp

PN 25, fläns / fläns, DN 100-500, reducerat genomlopp

Ventilhus	DN 100-500 Stål, P235GH (1.0345)
Kula	DN 100-500 Rostfritt stål, X5CrNi18-10 (1.4301)
Kultätning	DN 100-500 PTFE+C
Spindel	DN 100-500 Rostfritt stål, X8CrNiS18-9 (1.4305)
Spindeltätning	DN 100-500 NBR
Manövrering	DN 100-500 Ventil utrustad med manuell växel
Fläns	EN 1092-1
	Tillgänglig PN 10, 16, 25, 40



Funktionsvillkor


-40 °C - +70 °C

Över 70 °C kontakta tillverkaren

Under -30 °C kontakta tillverkaren


Lägsta tillåtna omgivningstemperatur -40°C

Läckageklass A (EN 12266-1)




Ej för ånga

DN 100-600



DN 100-600



DN	PN	Product no.	A	B	C	D	D1	D2	D3	D4	E	H1	L	kg
100	25	280592	186	206	53	80	235.0	190.0	22.0	125.0	248	114	300	26.0
125	25	280593	224	216	53	100	270.0	220.0	26.0	200.0	258	112	325	35.0
150	25	280594	224	236	53	125	300.0	250.0	26.0	200.0	279	118	350	44.0
200	25	280596	268	244	69	150	360.0	310.0	26.0	250.0	293	92	400	78.0
250	25	280597	301	294	97	200	425.0	370.0	30.0	300.0	345	108	500	134.0
300	25	280598	363	343	118	250	485.0	430.0	30.0	500.0	412	115	500	205.0
350	25	280595	363	418	118	290	555.0	490.0	33.0	500.0	487	192	706	295.0
400	25	280599	444	500	138	340	620.0	550.0	36.0	500.0	573	242	810	408.0
500	25	280500	475	576	180	390	730.0	660.0	36.0	500.0	648	259	978	640.0